

BAOYU PPF Factory

Covestro High Transparent TPU PPF SPECIFICATION SHEET



Picture	Product	Thickness	Micron	UVR	Tensile Strength	Elongation at break	Puncture Resistance	Transparent Brightness	Self-Healing	Coating thickness	OMS conforms to ISO9001:	Size
	TT-KSC	6.5mil	165	100.0%	31.8MPa	215%	78.2N	133	Hot Fix	8um clear water coating	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	TB-150KSC	7.5mil	190	99.8%	42.2MPa	225%	91.2N	136	Hot Fix	8um clear water coating	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	TC-175KSC	8.5mil	215	99.8%	40.3MPa	237%	99.9N	135	Hot Fix	8um clear water coating	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	TD-215KSC	10mil	254	99.6%	42.7MPa	287%	122.7N	139	Hot Fix	8um clear water coating	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	TBS-150KSC	7.5mil	190	99.4%	38.3MPa	268%	78.3N	136	Hot Fix	15um hydrophobic	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	TCS-175KSC	8.5mil	215	99.8%	45.2MPa	328%	84.3N	138	Hot Fix	15um hydrophobic	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	BS-GLS-150KSC	7.5mil	190	100.0%	30.9MPa	280%	62.6N	137	Quick Fix	High-strength anti-fouling	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	BS-GLS-175KSC	8.5mil	215	100.0%	38.3MPa	290%	70.3N	139	Quick Fix	High-strength anti-fouling	GB/T 19001-2016/ISO 9001:2015	60in*50ft

Warranty: 8 years (No delamination, no residue, no hydrolysis, anti-aging)

Process: Cast extrusion molding, Covestro high brightness, high elasticity TPU polyurethane masterbatch+Bostik glue+hot repair scratch resistant coating

Glossy Black /Matte TPU PPF SPECIFICATION SHEET

Picture	Product	Thickness	Micron	UVR	Tensile Strength	Elongation at break	Puncture Resistance	Transparent Brightness	Self-Healing	Coating thickness	OMS conforms to ISO9001:	Size
	White matte 150KSC	7.5mil	190	100.0%	42.1MPa	196%	45.5N	/	Hot Fix	8um Hydrophobic Coating	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Black matte 150KSC	7.5mil	190	100.0%	36.6MPa	205%	68.6N	/	Hot Fix	8um Hydrophobic Coating	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Glossy Black 150KSC	7.5mil	190	100.0%	38.6MPa	210%	75.5N	133	Hot Fix	8um Hydrophobic Coating	GB/T 19001-2016/ISO 9001:2015	60in*50ft

Warranty: 8 years (No delamination, no residue, no hydrolysis, anti-aging)

Process: Cast extrusion molding, Covestro high brightness, high elasticity TPU polyurethane masterbatch+Bostik glue+hot repair scratch resistant

Wanhua TPU PPF SPECIFICATION SHEET

Picture	Product	Thickness	Micron	UVR	Tensile Strength	Elongation at break	Puncture Resistance	Transparent Brightness	Self-Healing	Coating thickness	OMS conforms to ISO9001:	Size
	WHSB -150	7.5mil	190	100.0%	42.1MPa	196%	158.5N	/	Hot Fix	15um clear water coating	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	WHSB-175	8.5mil	215	100.0%	45.2MPa	328%	179.9N	/	Hot Fix	15um clear water coating	GB/T 19001-2016/ISO 9001:2015	60in*50ft

Warranty: 8 years (Non-yellowing)

Process: Wanhua U9, Hydrophobic & High Anti-fouling Coating

Lubrizol Ultra Brightness Transparent TPU Does Not Yellen PPF SPECIFICATION



Picture	Product	Thickness	Micron	UVR	Tensile Strength	Elongation at break	Puncture Resistance	Transparent Brightness	Self-Healing	Coating thickness	OMS conforms to ISO9001:	Size
	BY-150LBR	7.5mil	190	99.9%	41MPa	225%	91.3N	156	Hot Fix	15um high gloss coating	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	BY-175LBR	8.5mil	215	99.9%	52MPa	236%	99.2N	158	Hot Fix	15um high gloss coating	GB/T 19001-2016/ISO 9001:2015	60in*50ft









Warranty: 10 years (No delamination, no residue, no hydrolysis, anti-aging)

Process: Cast extrusion molding, Lubrizol high gloss, high elasticity TPU polyurethane masterbatch+Bostik glue+Korean Cashew second repair scratch resistant coating

TPU color modified paint protection film series PPF SPECIFICATION SHEET

Picture	Product	Thickness	Micron	UVR	Tensile Strength	Elongation at break	Puncture Resistance	Transparent Brightness	Self-Healing	Coating thickness	OMS conforms to ISO9001:	Size
	Colorful Pupil Diamond	7.5mil	190	99.9%	42.3MPa	341%	59.3N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Colorful Green Diamond	7.5mil	190	99.9%	43.2MPa	343%	59.3N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Colorful Blue Diamond	7.5mil	190	99.9%	41.3MPa	344%	58.9N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Colorful Silver Diamond	7.5mil	190	99.7%	43.6MPa	335%	59.6N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Colorful Gold Diamond	7.5mil	190	99.8%	42.5MPa	339%	57.7N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Grandmother Stone Green	7.5mil	190	100.0%	43.9MPa	326%	59.3N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Lava Orange	7.5mil	190	100.0%	41.3MPa	290%	51.3N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Competition Orange	7.5mil	190	100.0%	40.2MPa	296%	50.2N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Mamba Green	7.5mil	190	100.0%	41.3MPa	322%	51.3N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Dreamy Volcano Grey(Deep)	7.5mil	190	100.0%	43.2MPa	335%	58.6N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Colorful Sky Blue	7.5mil	190	100.0%	42.3MPa	289%	52.6N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Grandmother Stone Green	7.5mil	190	100.0%	43.2MPa	337%	59.3N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Colorful Black	7.5mil	190	100.0%	42.3MPa	325%	58.6N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Dreamy Volcano Grey	7.5mil	190	100.0%	46.2MPa	323%	57.3N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Light Gray Light Film	7.5mil	190	100.0%	49.3MPa	298%	51.5N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Byron Bay Blue	7.5mil	190	100.0%	48.2MPa	315%	53.5N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Twilight Purple	7.5mil	190	100.0%	47.3MPa	340%	59.6N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	AMG Mountain Grey	7.5mil	190	100.0%	43.2MPa	323%	58.3N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Ultra Bright Metallic Gray	7.5mil	190	100.0%	42.3MPa	324%	57.3N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Metal Aluminum Mercury	7.5mil	190	100.0%	45.2MPa	315%	56.8N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Urban Cuizhu	7.5mil	190	100.0%	42.3MPa	341%	58.3N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Magic Flame Green	7.5mil	190	100.0%	43.2MPa	315%	59.3N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Flower Pink	7.5mil	190	100.0%	46.9MPa	312%	57.5N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Black Crystal Ice Armor	7.5mil	190	100.0%	43.8MPa	289%	54.3N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Metallic white	7.5mil	190	100.0%	42.3MPa	312%	58.3N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Liquid Metal Somato Blue	7.5mil	190	100.0%	43.1MPa	323%	56.3N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Liquid Metal Gentian Blue	7.5mil	190	100.0%	42.3MPa	326%	56.7N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Super bright Metal Gun Gray	7.5mil	190	100.0%	43.2MPa	314%	57.3N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Diamond Pearl Black	7.5mil	190	100.0%	42.4MPa	297%	55.2N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft

	Havana Black	7.5mil	190	100.0%	48.2MPa	289%	54.3N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	White to Diamond Red	7.5mil	190	99.8%	49.9MPa	314%	54.1N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	White to Diamond Green	7.5mil	190	99.7%	43.2MPa	316%	57.5N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	White to Diamond Purple	7.5mil	190	99.8%	45.1MPa	320%	59.5N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	White to Diamond Orchid	7.5mil	190	99.9%	43.2MPa	316%	56.2N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	carbon fibre	7.5mil	190	100.0%	42.9MPa	279%	51.0N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Midnight Purple	7.5mil	190	100.0%	41.2MPa	289%	53.5N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Jaguar British Green	7.5mil	190	100.0%	42.3MPa	325%	56.3N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Jinsha Stone Green	7.5mil	190	100.0%	43.2MPa	321%	57.5N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Blue Crystal Ice Armor	7.5mil	190	100.0%	47.8MPa	298%	52.7N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Cherry Red	7.5mil	190	100.0%	43.7MPa	312%	54.3N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Diamond Pearl Grey	7.5mil	190	100.0%	43.3MPa	324%	58.6N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Champagne Gold (Deep)	7.5mil	190	100.0%	43.9MPa	313%	59.1N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	White to Diamond Gold	7.5mil	190	99.9%	44.3MPa	325%	58.3N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Ceramic white (matte)	7.5mil	190	99.9%	43.8MPa	314%	56.8N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Dreamy Grey Charm Green	7.5mil	190	100.0%	42.3MPa	316%	59.7N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Stars radiating across the sky	7.5mil	190	100.0%	43.2MPa	298%	59.6N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Colorful Gold Green	7.5mil	190	100.0%	47.3MPa	312%	51.2N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Beetroot Purple	7.5mil	190	100.0%	43.9MPa	285%	51.2N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Ultra matte AMG mountain gray	7.5mil	190	100.0%	42.3MPa	287%	59.6N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Matte	7.5mil	190	99.9%	43.2MPa	319%	56.2N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Pearlescent Blue Grey	7.5mil	190	100.0%	42.3MPa	298%	51.5N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Silver Illusion Purple	7.5mil	190	100.0%	48.8MPa	315%	54.3N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Obsidian Black	7.5mil	190	100.0%	48.3MPa	311%	59.1N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	White to Diamond Pine Green	7.5mil	190	99.9%	46.2MPa	321%	57.2N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	pearl black	7.5mil	190	100.0%	42.3MPa	321%	59.5N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Metal Mountain Green	7.5mil	190	100.0%	43.8MPa	314%	57.2N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Chameleon Purple Blue Green	7.5mil	190	100.0%	45.6MPa	316%	54.1N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Chameleon Blue Gold Green	7.5mil	190	100.0%	48.7MPa	317%	59.3N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Black Rose	7.5mil	190	100.0%	48.6MPa	323%	58.2N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Chameleon Red Blue Green	7.5mil	190	100.0%	44.6MPa	308%	59.5N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Metal Black Gold	7.5mil	190	100.0%	47.9MPa	309%	59.3N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Liquid metal gray	7.5mil	190	100.0%	45.2MPa	342%	59.1N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Pearlescent white	7.5mil	190	100.0%	42.3MPa	332%	57.6N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	liquid silver	7.5mil	190	100.0%	43.2MPa	323%	51.2N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Dragon Blood Red	7.5mil	190	100.0%	42.8MPa	296%	50.1N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Radiant White	7.5mil	190	100.0%	43.2MPa	340%	59.3N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Chameleon Gold Red Purple	7.5mil	190	100.0%	42.3MPa	316%	58.2N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Huayue Powder	7.5mil	190	100.0%	43.2MPa	317%	59.1N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft

	Shadow Blue	7.5mil	190	100.0%	44.5MPa	313%	46.2N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Mirror Sky Pink	7.5mil	190	100.0%	43.2MPa	296%	44.1N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Pearl Orchid Grey	7.5mil	190	100.0%	42.7MPa	289%	48.3N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Dreamy Grey Charm Purple	7.5mil	190	100.0%	39.6MPa	296%	43.2N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Moran Yellow	7.5mil	190	100.0%	38.9MPa	294%	41.5N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Agate green	7.5mil	190	100.0%	43.2MPa	299%	43.2N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Skin feels like dragon blood red	7.5mil	190	100.0%	42.3MPa	278%	40.2N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Porsche Ashian Grey	7.5mil	190	100.0%	43.2MPa	289%	41.0N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Skin texture khaki green	7.5mil	190	100.0%	38.3MPa	280%	43.1N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Nado Grey(Deep)	7.5mil	190	100.0%	43.2MPa	296%	41.2N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Lava Orange	7.5mil	190	100.0%	46.5MPa	290%	41.0N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Soft Peach	7.5mil	190	100.0%	43.2MPa	289%	43.5N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Lizard Green	7.5mil	190	100.0%	42.9MPa	291%	41.5N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Transparent carbon fiber	7.5mil	190	96.5%	43.5MPa	330%	41.3N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	High gloss khaki green	7.5mil	190	100.0%	39.3MPa	290%	43.1N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Glacier Blue	7.5mil	190	100.0%	43.2MPa	298%	41.2N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Skin feel Porsche sub gray	7.5mil	190	100.0%	42.3MPa	289%	41.3N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Black Warrior	7.5mil	190	100.0%	38.5MPa	290%	41.5N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Ultra Bright Dark Green	7.5mil	190	100.0%	38.9MPa	298%	42.1N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Deep Blue	7.5mil	190	100.0%	43.2MPa	297%	43.1N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Crystal Sky Blue	7.5mil	190	100.0%	42.7MPa	289%	41.5N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Matte Porsche Grey	7.5mil	190	100.0%	45.2MPa	287%	41.6N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Crystal Tiffany	7.5mil	190	100.0%	41.3MPa	296%	41.3N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Crystal Armor Green	7.5mil	190	100.0%	44.2MPa	289%	43.1N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Ruby red	7.5mil	190	100.0%	42.1MPa	290%	41.2N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Porcelain Blue	7.5mil	190	100.0%	46.3MPa	293%	43.1N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Porsche Ashian Grey	7.5mil	190	100.0%	42.5MPa	296%	41.2N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Repair Naduo Ash	7.5mil	190	100.0%	43.1MPa	296%	41.5N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Bright Black	7.5mil	190	100.0%	42.3MPa	289%	43.1N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Gemstone Blue	7.5mil	190	100.0%	41.2MPa	337%	48.3N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Glacier Orchid	7.5mil	190	100.0%	43.2MPa	291%	41.6N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	175um Bright Black	7.5mil	190	100.0%	43.2MPa	289%	43.1N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Light sensitive Black Charm Red	7.5mil	190	100.0%	42.3MPa	288%	42.5N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Crystal Rouge Powder	7.5mil	190	100.0%	43.2MPa	291%	43.1N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Python Green	7.5mil	190	100.0%	42.3MPa	298%	41.2N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Glossy Plano Black	7.5mil	190	100.0%	41.3MPa	290%	41.6N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Suede Sub Gray	7.5mil	190	100.0%	39.6MPa	296%	41.2N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Porcelain Blue	7.5mil	190	100.0%	38.9MPa	297%	43.1N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Ice Crystal White	7.5mil	190	99.6%	42.3MPa	299%	41.5N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft

	Oolong Milk Tea Pink	7.5mil	190	100.0%	41.1MPa	289%	43.1N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Deep orange	7.5mil	190	100.0%	38.6MPa	293%	41.3N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Sao Paulo Yellow	7.5mil	190	100.0%	43.2MPa	294%	42.0N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	McLaren Orange	7.5mil	190	100.0%	42.3MPa	291%	41.5N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Matte Black	7.5mil	190	100.0%	43.2MPa	290%	43.1N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	White to Black Light Film	7.5mil	190	100.0%	39.1MPa	290%	43.2N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Crystal Black	7.5mil	190	100.0%	43.2MPa	289%	41.3N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Glossy Black	7.5mil	190	100.0%	37.9MPa	293%	43.1N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Super Black	7.5mil	190	100.0%	41.6MPa	297%	41.2N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Smoked Black Lamp Film	7.5mil	190	100.0%	42.3MPa	288%	43.2N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Deep Black Light Film	7.5mil	190	100.0%	43.2MPa	289%	43.1N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Light Black Light Film	7.5mil	190	100.0%	42.3MPa	293%	41.0N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Desert Yellow	7.5mil	190	100.0%	41.4MPa	294%	43.1N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Audi Nado Grey	7.5mil	190	100.0%	42.8MPa	297%	41.2N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	dark red	7.5mil	190	100.0%	43.2MPa	291%	43.1N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Misty Grey Purple	7.5mil	190	100.0%	41.8MPa	294%	41.2N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft
	Bright Moon White	7.5mil	190	99.6%	42.5MPa	293%	41.0N	/	Hot Fix	15um	GB/T 19001-2016/ISO 9001:2015	60in*50ft

